CAD Algérie
Compagnie Algérienne de Distribution

CATALOGUE

CONFORT

Boilers, water heaters, storage heaters, radiators, multilayer pipe, nail-in clips

6 product sheets · Edition October 2026

Phone
023 85 69 68

E-mail
marketing@cad-dz.com

WhatsApp
0778 16 82 81

Heating & hot water



CONFORT EUROSTAR & MINI series

Wall-hung gas boilers

Central heating and instant domestic hot water, smart Wi-Fi control.

Features	MINI SERIE 24 kW	EUROSTAR 28 kW	EUROSTAR 35 kW
Thermal output	24.0 kW	28.0 kW	33.6 kW
Efficiency (rated output)	90 %	89 %	89 %
Heating temperature range	30 - 80 °C	30 - 80 °C	30 - 80 °C
DHW temperature range	30 - 60 °C	30 - 60 °C	30 - 60 °C
Control technology	Smart Wi-Fi	Smart Wi-Fi	Smart Wi-Fi
Electrical protection	IPX4D	IPX4D	IPX4D



CONFORT 5 L / 10 L

Gas water heater

Instant, continuous hot water, built-in ODS safety.

Features	10 L (CNF10GN20)	5 L (CNF5GN20)
Max. flow (ΔT 25 °C)	10 L/min	5 L/min
Heat output	17.2 kW	8.4 kW
Gas type	I2H-G20 mbar	I2H-G20 mbar
Safety system	Built-in (ODS device)	Built-in (ODS device)
Flue diameter	90 mm	90 mm
Pipe connection	G 1/2	G 1/2



CONFORT 50 L / 80 L

Electric storage water heater

Constant, safe hot water, simplified wall installation.

Features	TEEE 50 M	TEEE 80 M
Capacity	50 L	80 L
Power	1800 W	2000 W
Voltage / frequency	220-240 V / 50-60 Hz	220-240 V / 50-60 Hz
Operating pressure	6 bar	6 bar
Dimensions (D × H)	450 × 635 mm	450 × 870 mm
Empty weight	18.90 kg	23.90 kg



CONFORT 600/80 series

Aluminium radiators

Fast, even heat distribution, modular design.

Technical data (per section)	600/80 series
Overall height (A)	672 mm
Centre distance (B)	600 mm
Depth (D) / width (C)	80 mm / 80 mm
Water content	0.39 L
Section weight	1.1 kg
Output (ΔT = 50 °C)	114 W
Output (ΔT = 60 °C)	144 W

Plumbing



CONFORT Multilayer pipe · sleeved

Multilayer pipe

PEX-b / Al / PEX-b multilayer pipe, Ø 16 and Ø 20, for domestic hot and cold water and heating.

Diameters **Ø 16 and Ø 20 mm**	Structure **PEX-b / Al / PEX-b**	Maximum operating pressure **10 bar**
Operating temperature **max 95 °C**	Maximum peak temperature **110 °C**	Coils **100 m**

Characteristic	Ø 16	Ø 20
Wall thickness	2.0 mm	2.0 mm
Outside Ø (min. - max.)	16.0 - 16.3 mm	20.0 - 20.3 mm
Inside Ø (min. - max.)	11.4 - 12.3 mm	15.4 - 16.3 mm
Water content (per metre)	0.113 l	0.201 l
Bending radius without tools	5 × Ø	5 × Ø
Linear thermal expansion coefficient	0.026 mm/m·K	0.026 mm/m·K
Pipe roughness	0.007 mm	0.007 mm
Degree of cross-linking	> 65 %	> 65 %
Coil length	100 m	100 m
Bar length	On request	On request
Red and blue insulation thickness	6 mm	6 mm
White insulation thickness	10 mm	10 mm



CONFORT Nail-in clips

3 references

Nail-in fixing clips for one, two or four pipes.

Available references
COLLIER A FRAPPE MONO
COLLIER A FRAPPE DOUBLE
COLLIER A FRAPPE QUADRE

Points of sale

Algiers - TDM / LEO
0782080020 · 0782080017 · 0782082080

Algiers - CAD 2 / LEO
0550606068 · 0771667723 · 0773345657

Algiers - LEO Showroom
0550444448 · 0778635306

Algiers - LEO · CONFORT · EURO FLAMME after-sales service
0674811164

Constantine - CAD / LEO
0550370614 · 0550561351

Oran - LEO Showroom
0770005635

El Guerrara - CAD / LEO
0555064903 · 0668516022

Algiers - CAD 16 / LEO
0550838383 · 0550969696 · 028286014

Algiers - GFIPH SNTP
0550444449 · 0555980907

Algiers - Fpiscine
0550202028

El Eulma - LEO Showroom
0670191942 · 0670191943

Oran - CAD Oran
0555264742 · 0555264741

Djelfa - CAD / LEO
0550060674 · 0670191943

Ouargla - CAD / LEO
0555064903 · 0555064904

Photos and specifications are non-binding. Complete, up-to-date sheets on the CAD website.